

**GRAMER****HALLDORSON**

# Golden Fidelity

## OUTPUT TRANSFORMER

(PART NUMBER H--4111)

### FOR ULTRA-LINEAR APPLICATIONS

Every Gramer-Halldorson Golden Fidelity output transformer is registered by serial number.

A specific response curve throughout the range ( 10 to 100,000 cps) is provided with each unit. Certification of each unit is furnished with signatures of both Chief Engineer and Chief Inspector.

**HIGH-FREQUENCY RANGE EXTENDED BY HIGHLY SPECIALIZED WINDING TECHNIQUES.**

**EXTREMELY LOW RANGE IS ASSURED THROUGH USE OF GRAIN-ORIENTED HIGH SILICON CORE MATERIAL.**

**Primary** has screen taps for triode-tetrode operation.

**Secondary** is tapped for 4, 8, or 16 ohm voice coil.

### ELECTRICAL RATING

PRI. IMPED.	SEC. IMPED.	FREQUENCY RESPONSE*	MAX. WATTS	MAX. PRI. DC/HALF
7400†	4/8/16	± 1/2 db 10 to 100,000 cps	40	100 MA.

†For Ultra-Linear Operation

\*Normal in a Williamson Type Amplifier at 10 watt level.



### GOLD-PLATED CASE

Each Gramer-Halldorson Golden Fidelity Output Transformer is unconditionally guaranteed against electrical defects.

**SIZE:** 4¼" x 4⅞" x 3⅝"

**MTG. CENTERS:** 2¾" x 3⅞"

**SHIPPING WEIGHT:** 7¼ lbs.

**LIST PRICE: \$41.25**

**GRAMER***Halldorson***TRANSFORMER CORPORATION**

2734 NORTH PULASKI ROAD • CHICAGO 39, ILLINOIS